Rheem *Classic*® Series Air Conditioners



RA16 Series

Efficiencies up to 16 SEER/13 EER Nominal Sizes 11/2 to 5 Ton [5.28 to 17.6 kW] Cooling Capacities 17.3 to 60.5 kBTU [5.7 to 17.7 kW]











"Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet Energy Star. Ask your Contractor for details or visit www.energystar.gov."

- New composite base pan dampens sound, captures louver panels, eliminates corrosion and reduces number of fasteners needed
- Powder coat paint system for a long lasting professional finish
- Scroll compressor uses 70% fewer moving parts for higher efficiency and increased reliability
- Modern cabinet aesthetics increased curb appeal with visually appealing design
- Curved louver panels provide ultimate coil protection, enhance cabinet strength, and increased cabinet rigidity
- Optimized fan orifice optimizes airflow and reduces unit sound
- Rust resistant screws confirmed through 1500-hour salt spray testing
- PlusOneTM Expanded Valve Space 3"-4"-5" service valve space – provides a minimum working area of 27-square inches for easier access
- PlusOneTM Triple Service Access 15" wide, industry leading corner service access makes repairs easier and faster.
 The two fastener removable corner allows optimal access to internal unit components. Individual louver panels come out once fastener is removed, for faster coil cleaning and easier cabinet reassembly

- Diagnostic service window with two-fastener opening provides access to the high and low pressure.
- External gauge port access allows easy connection of "low-loss" gauge ports
- Single-row condenser coil makes unit lighter and allows thorough coil cleaning to maintain "out of the box" performance
- 35% fewer cabinet fasteners and fastener-free base allow for faster access to internal components and hassle-free panel removal
- Service trays hold fasteners or caps during service calls
- QR code provides technical information on demand for faster service calls
- Fan motor harness with extra long wires allows unit top to be removed without disconnecting fan wire.